

In re Patent Application of
GORSUCH ET AL.
Serial No. Not Yet Assigned
Filed: Herewith

In the Specification:

Please replace the paragraph beginning at page 1,
line 2, with the following rewritten paragraph:

This application is a Continuation of pending U.S.
Application No. 10/345,791 filed January 16, 2003 entitled
"Dynamic Bandwidth Allocation to Transmit a Wireless Protocol
Across a Code Division Multiple Access (CDMA) Radio Link,
which is a Continuation of U.S. Application No. 09/596,425
filed June 19, 2000, now U.S. Patent No. 6,526,281 entitled
"Dynamic Bandwidth Allocation to Transmit a Wireless Protocol
Across a Code Division Multiple Access (CDMA) Radio Link,"
which in turn is a Continuation of U.S. Application No.
08/992,760 filed December 17, 1997, now U.S. Patent No.
6,081,536 entitled "Dynamic Bandwidth Allocation to Transmit a
Wireless Protocol Across a Code Division Multiple Access
(CDMA) Radio Link," which itself claims the benefit of U.S.
Provisional Application No. 60/050,338 filed June 20, 1997
entitled "Dynamic Bandwidth Allocation to Transmit a Wireless
Protocol Across a Code Division Multiple Access (CDMA) Radio
Link," and U.S. Provisional Application No. 60/050,277 filed
June 20, 1997 entitled "Protocol Conversion and Bandwidth
Reduction Technique Providing Multiple nB+D ISDN Basic Rate
Interface Links Over a Wireless Code Division Multiple Access
Communication System," the entire teachings of all of which
are incorporated herein by reference.

In re Patent Application of
GORSUCH ET AL.
Serial No. Not Yet Assigned
Filed: Herewith

Please delete the Summary of the Invention section beginning on page 4, line 6 in its entirety and add the following Summary of the Invention section:

SUMMARY OF THE INVENTION

In view of the foregoing background, an object of the present invention is to provide high speed data and voice service over standard wireless connections via a unique integration of ISDN protocols and existing cellular signaling such as is available with Code Division Multiple Access (CDMA) type digital cellular systems.

This and other objects, advantages and features in accordance with the present invention are provided by a base station for providing wireless communication of digital signals over a plurality of digital communication paths, with the digital signals being communicated using at least one radio frequency channel via CDMA modulated radio signals.

The base station comprises a wireless transceiver for establishing a communication session over a first digital communication path, and a bandwidth management module is connected to the wireless transceiver for allocating at least one code channel within the at least one radio frequency channel for exchanging digital signals over the first digital communication path during the communication session. The at least one code channel may include at least one traffic portion that is established for a predetermined time and at least one control portion that is continuously available.

The bandwidth management module may reallocate the at least one traffic portion from the first digital communication path to a second digital communication path if an extension of time is not requested from the base station

In re Patent Application of
GORSUCH ET AL.
Serial No. Not Yet Assigned
Filed: Herewith

over the first digital communication path for the at least one traffic portion, or if the base station no longer has digital signals to transmit over the first digital communication path via the at least one traffic portion, but with the at least one reallocated traffic portion appearing as though it is still continuously available to the first digital communication path.

The at least one code channel may comprise a single code channel, and the traffic and control portions are multiplexed on the single code channel. Alternatively, the at least one code channel may comprise a plurality of code channels, and the traffic and control portions are on separate code channels.

The bandwidth management module may reallocate the at least one traffic portion from the second digital communication path to the first digital communication path if a request for transmitting digital signals is received via the at least one control portion over the first digital communication path. Alternatively, the bandwidth management module may reallocate the at least one traffic portion from the second digital communication path back to the first digital communication path if the base station no longer has a need to transmit digital signals over the second digital communication path.

The digital signals may comprise voice and/or data signals. In addition, the wireless communication of digital signals may be provided with a first subscriber unit over the first digital communication path, and with a second subscriber unit over the second digital communication path. The at least one radio frequency channel may comprise a first radio frequency channel for establishing a forward code channel

In re Patent Application of
GORSUCH ET AL.
Serial No. Not Yet Assigned
Filed: Herewith

between the wireless transceiver and the first subscriber unit, and a second radio frequency channel for establishing a reverse code channel between the first subscriber unit and the wireless transceiver. The bandwidth management module may assign both the forward and reverse code channels. The forward and reverse code channels may be multiplexed on a single radio frequency channel, or they may be on different radio frequency channels.

In addition, the wireless transceiver may also establish a communication session with a data network so that the first subscriber unit and the data network exchange digital signals over the first digital communication path, and when the first subscriber unit does not request an extension of time for the at least one traffic portion, or if the data network no longer has digital data to transmit to the first subscriber unit, or if the base station no longer has digital data to transmit to the first subscriber unit or the data network, then the bandwidth management module reallocates the at least one traffic portion from the data network, but with the at least one reallocated traffic portion appearing as though it is still continuously available to the data network over the first digital communication path.

Another aspect of the present invention is directed to a subscriber unit for providing wireless communication of digital signals between terminal equipment connected therewith and a first digital communication path. The digital signals may be communicated using at least one radio frequency channel via Code Division Multiple Access (CDMA) modulated radio signals. The subscriber unit comprises a wireless transceiver for establishing a communication session over the first digital communication path, and a bandwidth management module

In re Patent Application of
GORSUCH ET AL.
Serial No. Not Yet Assigned
Filed: Herewith

is connected to the wireless transceiver.

The bandwidth management module receives over the first digital communication path at least one allocated code channel within the at least one radio frequency channel to exchange digital signals during the communication session. The at least one allocated code channel may include at least one traffic portion that is established for a predetermined time and at least one control portion that is continuously available.

If the bandwidth management module does not request an extension of time over the first digital communication path for the at least one traffic portion, or if there is no longer a need to transmit digital signals to the subscriber unit over the first digital communication path, then the at least one traffic portion is reallocated to a second digital communication path associated with a second subscriber unit. A spoofing module may be connected to the bandwidth management module so that the reallocated traffic portion appears as though it is still continuously available to the wireless transceiver over the first digital communication path.

Yet another aspect of the present invention is directed to a digital communication system comprising base stations and subscriber units as defined above.